



VZDUCHOVODY

Zajišťují přívod a odvod vzduchu z místnosti

Ohebné potrubí - ALU

- Materiál - hliník
- Síla stěny 100 mikronů
- Teplota -30 až +250°C



Ohebné potrubí - ALU

Výkres	Obj. č.	Typ	Rozměry		Max. tlak (Pa)	Bal./ks
			ØD (mm)	L (m)		
	1009950	100/1	102	1	10 000	1 / 30
	1009951	100/3	102	3	10 000	1 / 90
	1009952	100/6	102	6	10 000	1 / 20
	1009953	125/1	127	1	10 000	1 / 20
	1009954	125/3	127	3	10 000	1 / 56
	1009955	125/6	127	6	10 000	1 / 12
	1009958	150/1	152	1	10 000	1 / 14
	1009956	150/3	152	3	10 000	1 / 42
	1009959	150/6	152	6	10 000	1 / 9
	1009957	160/3	162	3	10 000	1 / 30
	1009849	200/3	202	3	10 000	1 / 22
	1009850	250/3	252	3	10 000	1 / 12
	1009851	315/3	317	3	10 000	1 / 9



Ohebné potrubí - POLYVENT

- Hliníková fólie s tenkou vrstvou polyesteru
- Spirála z ocelového drátu
- Síla stěny 0,8 - 1,5 mm
- Teplota -30 až +250°C



Ohebné potrubí - POLYVENT

Výkres	Obj. č.	Typ	Rozměry		Max. tlak (Pa)	Bal./ks
			ØD (mm)	L (m)		
	1009457	605-M0	102	1,5	3 000	1
	1009458	605-M0	102	3	3 000	1
	1009459	605-M0	102	10	3 000	1
	1009460	605-M0	127	1,5	3 000	1
	1009461	605-M0	127	3	3 000	1
	1009462	605-M0	127	10	3 000	1
	1009463	605-M0	152	1,5	3 000	1
	1009464	605-M0	152	3	3 000	1
	1009465	605-M0	152	10	3 000	1
	1009468	605-M0	315	10	3 000	1




Mezikus (spojka)

- Materiál - PVC
- Propojení T kusů, kolen atd.



Mezikus (spojka)

Výkres	Obj. č.	Typ	Rozměry (mm)			Bal./ks
			ØD	ØD1	a	
	1001113	1113	100	103	60	1 / 20
	1002123	2123	125	128	60	1 / 15
	1003133	3133	150	153	60	1 / 10



Spojka vnitřní

- Materiál - PVC
- Nasazuje se dovnitř potrubí



Spojka vnitřní

Výkres	Obj. č.	Typ	Rozměry (mm)			Bal./ks
			ØD	ØD1	a	
	1001110	111	100	96	62	1 / 20
	1002120	212	125	123	62	1 / 16
	1003130	313	150	148	62	1 / 28
	1004140	414	200	197	62	1 / 10

