





Připojovací svorkovnice, 6-50qm², 54 mm


Typ **BBA-TP3/50**
 Catalog No. **107183**

Dodavatelský program


Sortiment			60mm systém
Základní funkce			Svorky
Dílčí sortiment			Připojovací svorkovnice
Materiál			Bez silikonu, bez chlóru
Samozhášecí			podle UL 94
Odolnost proti plazivým proudům			CTI 200
Odolný proti teplotám			do 120°C
Popis			Odnímatelné svorky k připojení průchozích vodičů Okruhování je možné
Terminal area W x H		mm	10 x 15
Šířka		mm	54
Póly			3
Jmenovitý proud	le	a	300
Vodič			6 - 50 mm ² AWG 10 - AWG 2/0.   # 6 x 9 x 0.8
Cu factor		kg	0,03
Použitelný pro			12 x 5/10 15 x 5/10 20 x 5/10 25 x 5/10 30 x 5/10
Použitelné pro			Double T profile

Upozornění

 round conductor, solid


 Flexible, round conductor with correctly crimped ferrule

Round conductor, stranded

 Section conductor, solid

Sector conductor, stranded

CU band

 CU busbar

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E300273
UL Category Control No.			NMTR, NMTR7
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL listed, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits

Rozměry

