









Propojovací svorka 4-35mm², 10 mm

Typ AKU35/10
Catalog No. 107192

Dodavatelský program

Sortiment			60mm systém 185mm systém Kompaktní systém
Základní funkce			Svorky
Dílčí sortiment			Univerzální připojovací svorky
Popis			s integrovanou pružinou, otevřenou připojovací mezerou a neztratitelným šroubem
Terminal area W x H		mm	10.5 x 11
Šířka		mm	15.5
Jmenovitý proud	le	a	270
Vodič			4 - 35 mm ² AWG 10 - AWG 2. přímo svorkovaná:    # 3 x 9 x 0,8 mm nebo 6 x 9 x 0,8 mm
Použitelné pro			All 10 mm thick flat busbars
Upozornění			
○ round conductor, solid			
 Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
 Section conductor, solid			
Sector conductor, stranded			
# CU band			
 CU busbar			

aprobace,

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits

