


**Profilová svorka 41x20-42**
**Typ**    **AKP800**  
**Catalog No.**                                **107198**
**Dodavatelský program**

Sortiment			60mm systém 185mm systém
Dílčí sortiment			Profilové svorky
Popis			Připojení ke sběrnicím bez vrtání děr Při paralelním připojení lamelových měděných lišt vložte distanční členy
Šířka		mm	72
Jmenovitý proud	le	a	1600
Vodič			800 mm <sup>2</sup> , připojovací prostor 41 x 20 - 42 mm ■ #
Cu factor		kg	0,20
Použitelné pro			Double T profile
<b>Upozornění</b>			
○ round conductor, solid			
⊗ Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
💡 Section conductor, solid			
Sector conductor, stranded			
# CU band			
■ CU busbar			

**aprobace,**

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits