



Výměnný modul pro svodič SPDT3 335V AC, 2,5kA pro svodič SPDT3

Typ SPDT3-335
Catalog No. 170486
Alternate Catalog No. SPDT3-335

EATON
Powering Business Worldwide™

Dodavatelský program

Výrobky		svodiče přepětí
Oblast použití		Obytná budova Průmyslová budova Volné plochy

Technická data podle ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)

Elektrotechnika, automatizacní technika a technika řízení procesu / Ochranné zařízení, přístroj / Svod prepětí / Surge protection device for power supply systems (ecl@ss10.0.1-27-13-08-05 [ACN278011])

System configuration DC		No
System configuration IT		No
System configuration TN		No
System configuration TN-C		No
System configuration TN-C-S		No
System configuration TN-S		No
System configuration TT		No
System configuration other		Yes
Number of conductors (without earthing)		0
Nominal discharge surge current (8/20)	kA	2.5
Nominal voltage AC	V	335
Nominal voltage DC	V	0
Short-circuit breaking capacity (Iscsr)	kA	0
Max. continuous voltage AC	V	335
Max. discharge surge current (8/20)	kA	10
Max. continuous voltage DC	V	0
Mounting method		On basic element
Construction size		1 modular spacing
Max. PV-voltage	V	0
Voltage protection level	kV	1.6
Max. conductor cross section solid (solid, stranded)	mm ²	25
Max. conductor cross section flexible (fine-strand)	mm ²	0
Voltage protection level L-N	kV	0
Voltage protection level N-PE	kV	0
With remote signalling contact		No
Integrated backup fuse		No
Signalling at the device		Optic
Category type 2		No
Degree of protection (IP)		IP20