



Typ  
Catalog No. IZMX-CT40-N-1  
Alternate Catalog No. 183991  
70C1718G11

### Dodavatelský program

Sortiment		Příslušenství
Accessories		Current sensor for neutral conductor
		The external transformer is required for the earth-fault protection. a) For the neutral conductor in the case of 3-pole circuit-breakers b) For directly measuring the ground fault current at the grounded neutral point in the case of 3-pole and 4-pole circuit-breakers.
Sloupek		3
Použitelný pro		IZMX-DTV-G +IZMX-DTV-G +IZMX-DTV-GZ +IZMX-DTU-A IZMX-DTU-A +IZMX-DTU-AZ +IZMX-DTU-G IZMX-DTU-G +IZMX-DTU-AM IZMX-DTU-AM +IZMX-DTU-AMZ IZMX-DTU-GMZ IZMX-DTU-GM +IZMX-DTU-GM +IZMX-DTU-GZ IZMX-DTP-G IZMX-DTP-G +IZMX-DTP-GZ +IZMX-DTP-GM +IZMX-DTP-GMZ IZMX-DTP

### Ověření návrhu podle ČSN EN 61439

Technické údaje pro ověření konstrukce			
Provozní teplota okolí min.		°C	-25
Provozní teplota okolí max.		°C	70

### Technická data podle ETIM 7.0

Low-voltage industrial components (EG000017) / Current transformer (EC002048)			
Elektrotechnika, automatizační technika a technika řízení procesu / Zpracování signálu / Prevodník / Prevodník proudu (ecl@ss10.0.1-27-21-09-02 [AAB626014])			
Model			Wound primary current converter
Primary rated current		A	4000
Secondary rated current		A	0
Secondary rated apparent power		VA	0
Accuracy class			1
Over current limiting factor			
Calibrated			No
With shock protection			No
Height opening		mm	0
Width opening		mm	0
Opening diameter		mm	0
Snap mounting			No
With copper rail			No
Secondary connection			Screw connection
Number of primary inputs			1