



**Snímač pohybu**

**Typ  
Catalog No.**

**CBMD-02/02  
300919**

### Dodavatelský program

|              |  |                                |
|--------------|--|--------------------------------|
| Typ produktu |  | Senzor                         |
| Typ montáže  |  | Zabudovaný<br>Povrchová montáž |
| Napájení     |  | Baterie<br>Síťové napájení     |
| Typ snímače  |  | Pohyb<br>Přítomnost            |
| Barva        |  | Tryskově černá                 |

### Technická data podle ETIM 7.0

|  |  |     |                 |
|--|--|-----|-----------------|
| Installation bus systems (EG000032) / Movement sensor for bus system (EC001582)  |  |     |                 |
| Elektrotechnika, automatizační technika a technika řízení procesu / Elektroinstalacní zařízení, přístroj / Sbernicový systém / Movement sensor for bus system (ecl@ss10.0.1-27-14-31-44 [ACN421011]) |  |     |                 |
| Bus system KNX   |  |     | No              |
| Bus system KNX radio   |  |     | No              |
| Bus system radio frequent  |  |     | Yes             |
| Bus system LON   |  |     | No              |
| Bus system Powernet  |  |     | No              |
| Other bus systems  |  |     | xComfort        |
| Radio frequent bidirectional   |  |     | Yes             |
| Model  |  |     | Movement sensor |
| Mounting method  |  |     | Other           |
| Material   |  |     | Plastic         |
| Material quality   |  |     | Thermoplastic   |
| Surface protection   |  |     | Untreated       |
| Surface finishing  |  |     | Matt            |
| Colour   |  |     | Black           |
| RAL-number (akin)  |  |     | 9005            |
| Transparent  |  |     | No              |
| Bus connection included  |  |     | Yes             |
| Substation input   |  |     | No              |
| Creep-under protection   |  |     | No              |
| Operation mode switch  |  |     | No              |
| Animal zone  |  |     | No              |
| Staircase monitoring   |  |     | No              |
| Response value luminosity adjustable   |  |     | Yes             |
| Teach-function for response value luminosity   |  |     | No              |
| Switch-off delay self-learning   |  |     | No              |
| Optimum mounting height  |  | m   | 2.5             |
| Max. transmission range sideways   |  | m   | 4               |
| Max. transmission range frontally  |  | m   | 8               |
| Diameter detection range on floor  |  | m   | 5               |
| Detection angle vertical   |  | °   | 90 - 90         |
| Detection angle horizontal   |  | °   | 90 - 90         |
| Number of channels   |  |     | 2               |
| Number of binary inputs  |  |     | 0               |
| Switching power  |  | W   | 0               |
| Min. switch-on time  |  | s   | 3               |
| Max. duty cycle  |  | min | 120             |

